

ROYAL PRODUCTS

For more information contact:

Royal Windows, Inc.
3109 East Randol Mill Road
Arlington, Texas 76011

2" CURVED PVC MINI BLINDS 2

2" CURVED PVC MINI BLINDS

Standard Features

- Durable 2" Curved PVC Slats
- Custom Molded 2 1/2" PVC Foam Valance
- 2" x 2 1/4" Headrail
- Cord Tilt
- Color Coordinated Components, Cords, Ladders
- Molded Vinyl Bottomrail

Colors Available

- White - P02
- Alabaster - P04

Options

- Cotton Tape 3/4" -- Add 10%
- Cotton Tape 1 1/2" -- Add 15%
- 2 Blinds on One Headrail -- Add 10%
- 3 Blinds on One Headrail -- Add 15%
- Valance Returns for Outside Mount -- No Charge
- Hold Down Brackets & Spacers -- No Charge
- Wand Tilt -- Not Available
- Tile Cut Out -- \$10.00 Net surcharge
- Control Locations -- No Charge

Standard - tilter left, lift cord right

Reverse - tilter right, lift cord left

Controls left, controls right

Under 13" will have center tilt only

FABRICATION

Verify actual opening dimensions by on-site measurement. Calculate blind dimensions to fit within specified tolerances.

Fabricate blinds to fill openings from head to sill and jamb-to-jamb.

Fabricate blinds to fill all exterior window openings except at doors, door sidelights and transoms unless noted.

EXECUTION

INSPECTION

Insure that the installation area is free of conditions that interfere with blind installation. Begin blind installation only when unsatisfactory conditions have been corrected.

INSTALLATION

Install blinds in accordance with manufacturer's procedures.

Install intermediate support brackets as needed to prevent deflection in headrail.

Install blinds with adequate clearance to permit smooth operation of blinds. Hold blinds 1/4-inch clear from each side of window opening on inside mount .

Set tilt and lift controls. Demonstrate blinds to be in smooth, uniform working order.

HORIZONTAL MINI BLIND SCHEDULE:

Provide blinds at the following locations: (listing of blind locations, control options, accessories and colors).